



NOTES

1. REFER TO WATER CYCLE MANAGEMENT GUIDELINES AND SQID GUIDELINES FOR DESIGN GUIDANCE
2. ENGINEERING WORKS TO BE DESIGNED IN ACCORDANCE WITH COUNCIL'S ENGINEERING DESIGN GUIDELINES
3. REFER TO COUNCIL'S LANDSCAPE DESIGN GUIDELINES FOR TOPSOIL, MULCH AND PLANTING SPECIFICATIONS.
4. CONCRETE APRON TO BE 25MPA WITH SL82 REINFORCING STEEL AND 150mm MINIMUM THICKNESS
5. MAINTENANCE ACCESS TRACK TO BE 2% STABILISED GRAVEL 3m WIDE AND 150mm MIN THICKNESS
6. ROCK FOR APRON STONE PITCHING TO BE 250-300mm HARD DURABLE ROCK IN ACCORDANCE WITH ENGINEERING GUIDELINES

SECTION A-A

VERSION	DATE	COMMENTS
06	6 AUG 16	REVISE NOTES
05	11 DEC 13	REVISE NOTES
04	18 OCT 12	REVISE NOTES
03	27 SEPT 12	UPDATE NOTES, REMOVE ROCK BEACHING FROM FOREBAY
02	10 JULY 12	ADD VEHICLE ACCESS DETAIL

WORK TO FIGURED DIMENSIONS - DO NOT SCALE - THIS DRAWING IS SUBJECT TO COPYRIGHT AND IS THE PROPERTY OF LAKE MACQUARIE CITY COUNCIL. PERSONS MUST NOT RELY ON THESE STANDARD DRAWINGS AS THE EQUIVALENT OF, OR A SUBSTITUTE FOR, PROJECT-SPECIFIC DESIGN & ASSESSMENT BY A QUALIFIED PROFESSIONAL.



126-138 MAIN ROAD
SPEERS POINT
PHONE (02)4921 0333
www.lakemac.com.au

DRAWING TITLE
BIORETENTION BASIN

DRAWING No. **EGSD-417** VERSION: **06**