



PAVEMENT DESIGNED TO HAVE SUFFICIENT STRENGTH FOR FULLY LADEN EDUCATOR TRUCK

CHECK VERTICAL CLEARANCE TO OVERHEAD ELECTRICITY IS SUFFICIENT IF A CRANE OR SIMILAR MAINTENANCE VEHICLE IS REQUIRED

1m CONCRETE PAD AROUND ACCESS COVER

GPT ACCESS COVER

SUITABLE PARKING BAY FOR AUSTRROADS STANDARD 8.8m VEHICLE

SIGN

SIGN

POWER POLE

ROLL KERB AND GUTTER

STORMWATER PIPE

NOTES

1. PROVIDE SUFFICIENT HORIZONTAL AND VERTICAL CLEARANCES TO STREET FURNITURE AND SERVICES. REFER TO RTA ROAD DESIGN GUIDELINES AND SERVICE AUTHORITY STANDARDS
2. PAVEMENT TO BE CONCRETE 25MPA WITH SL72 REINFORCING STEEL AND 150mm MIN THICKNESS, SUB-BASE TO BE FOR COMPACTED 95% AND 100mm MIN THICKNESS
3. PROVIDE CONCRETE ACCESS TO ALL ACCESS COVERS
4. SIGNS - NO STANDING 7AM TO 5PM MON-FRI

| | | | | | | | |
|---------|------------|---------------------------|--|--|--|--|-------------|
| 04 | 06 AUG 16 | REVISE DESIGN | WORK TO FIGURED DIMENSIONS - DO NOT SCALE - THIS DRAWING IS SUBJECT TO COPYRIGHT AND IS THE PROPERTY OF LAKE MACQUARIE CITY COUNCIL. PERSONS MUST NOT RELY ON THESE STANDARD DRAWINGS AS THE EQUIVALENT OF OR A SUBSTITUTE FOR PROJECT-SPECIFIC DESIGN & ASSESSMENT BY A QUALIFIED PROFESSIONAL. | | 126-138 MAIN ROAD SPEERS POINT PHONE (02)4921 0333 www.lakemac.com.au | DRAWING TITLE MAINTENANCE ACCESS UNDERGROUND GPT | VERSION: 04 |
| 03 | 18 OCT 12 | REVISE DESIGN | | | SHEET: 1 OF 1 | DRAWING No: EGSD-423 | |
| 02 | 27 SEPT 12 | INCREASE OFFSET FROM ROAD | | | | | |
| 01 | 10 JULY 12 | DRAFT ISSUE | | | | | |
| VERSION | DATE | COMMENTS | | | | | |